

**Description**

Cr Max Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398C6AB9
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-561-1720
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1398C6AB9 Specifications

<b>Fastener Length:</b>	0.787 Inches Maximum
<b>Head Style:</b>	Countersunk W/protruding Stud
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.190 Inches Nominal
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Grip Length:</b>	0.501 Inches Minimum And 0.562 Inches Maximum
<b>Countersink Angle:</b>	8.0 Degrees Nominal
<b>Material:</b>	Nickel Alloy Locking Ring
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Iron Alloy 660 Stem
<b>Surface Treatment:</b>	Passivate Sleeve

## How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C6AB9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.