

Description

Fastener Length: 11/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1398C88
Minimum Qty (MOQ):	5
NSN:	5320-01-334-2845
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N NAS1398C8-8 Specifications

Fastener Length:	0.698 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.253 Inches Maximum
Head Major Diameter:	0.475 Inches Minimum And 0.525 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Stem
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Sleeve
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring
Specification/standard Data:	80205-nas1398 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C8-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.