

Description

Fastener Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1398C8A4 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5320-00-559-7859 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1398C8A4 Specifications

| | |
|--|--|
| Fastener Length: | 0.448 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.107 Inches Minimum And 0.117 Inches Maximum |
| Shank Diameter: | 0.249 Inches Minimum And 0.253 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.475 Inches Minimum And 0.525 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Shear Strength: | 2450 Single Pounds Per Square Inch |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Iron Alloy 660 Stem |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Stem |
| Material Document And Classification: | Ams 5732 Assn Std 1st Material Response Sleeve Or Ams 5731 Assn Std 2nd Material Response Sleeve Or Ams 5737 Assn Std 3rd Material Response Sleeve |
| Specification/standard Data: | 80205-nas1398 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C8A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.