

Description

NAS1398 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1398CW3A3
Minimum Qty (MOQ):	15
NSN:	5320-01-608-3137
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1398CW3A3 Specifications

Fastener Length:	0.53 Inches Maximum
Head Style:	Brazier
Head Height:	0.04 Inches Minimum And 0.05 Inches Maximum
Shoulder Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shoulder Length:	0.291 Inches Maximum
Shank Diameter:	0.094 Inches Maximum
Shank Style:	Straight W/shoulder
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
End Item Identification:	E-3 Acft
Part Name Assigned By Controlling Agency:	Rivet-blind, Protruding Head, Locked Spindle
Material:	Steel Corrosion Resisting Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398CW3A3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.