

Description

NAS1398 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1398CW3A3
Minimum Qty (MOQ):	15
NSN:	5320-01-608-3137
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1398CW3A3 Specifications

<b>Fastener Length:</b>	0.53 Inches Maximum
<b>Head Style:</b>	Brazier
<b>Head Height:</b>	0.04 Inches Minimum And 0.05 Inches Maximum
<b>Shoulder Diameter:</b>	0.093 Inches Minimum And 0.097 Inches Maximum
<b>Shoulder Length:</b>	0.291 Inches Maximum
<b>Shank Diameter:</b>	0.094 Inches Maximum
<b>Shank Style:</b>	Straight W/shoulder
<b>Head Major Diameter:</b>	0.178 Inches Minimum And 0.196 Inches Maximum
<b>End Item Identification:</b>	E-3 Acft
<b>Part Name Assigned By Controlling Agency:</b>	Rivet-blind, Protruding Head, Locked Spindle
<b>Material:</b>	Steel Corrosion Resisting Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398CW3A3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.