

**Description**

NAS1398 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398CW4A4
Minimum Qty (MOQ):	5
NSN:	5320-01-608-3152
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1398CW4A4 Specifications

<b>Fastener Length:</b>	0.75 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Nominal
<b>Shoulder Diameter:</b>	0.125 Inches Minimum And 0.128 Inches Maximum
<b>Shoulder Length:</b>	0.385 Inches Maximum
<b>Shank Diameter:</b>	0.125 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Straight W/shoulder
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>End Item Identification:</b>	E-3 Block 404
<b>Special Features:</b>	Full Serrated Spindle
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment:</b>	Cadmium Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398CW4A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.