

Description

NAS1398 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1398CW4A4 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-01-608-3152 |
| Schedule B: | 7318.23.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1398CW4A4 Specifications

| | |
|---------------------------------|---|
| Fastener Length: | 0.75 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Nominal |
| Shoulder Diameter: | 0.125 Inches Minimum And 0.128 Inches Maximum |
| Shoulder Length: | 0.385 Inches Maximum |
| Shank Diameter: | 0.125 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Straight W/shoulder |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| End Item Identification: | E-3 Block 404 |
| Special Features: | Full Serrated Spindle |
| Material: | Iron Alloy 660 Overall |
| Surface Treatment: | Cadmium Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398CW4A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.