

Description

NAS1398 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1398CW4A4
Minimum Qty (MOQ):	5
NSN:	5320-01-608-3152
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1398CW4A4 Specifications

Fastener Length:	0.75 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Nominal
Shoulder Diameter:	0.125 Inches Minimum And 0.128 Inches Maximum
Shoulder Length:	0.385 Inches Maximum
Shank Diameter:	0.125 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight W/shoulder
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
End Item Identification:	E-3 Block 404
Special Features:	Full Serrated Spindle
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398CW4A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.