

## **P/N NAS1398CW5A3**

### **Description**

Fastener Length: 29/64

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1398CW5A3

Minimum Qty (MOQ): 10

NSN: 5320-01-332-2211

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1398CW5A3 Specifications**

Identification Code Color:	Natural
Fastener Length:	0.451 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Locking Ring
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5732 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Stem Or Ms 5732 Assn Std All Material Responses Stem Or Ams 5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment Document And Classification:	Aqq-p-416,ty 2,cl 2 Assn Std Single Treatment Response Sleeve
Specification/standard Data:	80205-nas1398 Professional/industrial Association Standard

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1398CW5A3">https://military-fasteners.com/rivets/blind+rivets/NAS1398CW5A3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1398CW5A3">https://military-fasteners.com/rivets/blind+rivets/NAS1398CW5A3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1398CW5A3">https://military-fasteners.com/rivets/blind+rivets/NAS1398CW5A3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1398CW5A3">https://military-fasteners.com/rivets/NAS1398CW5A3</a> and selecting the quantity you want <a href="https://military-fasteners.com/rivets/NAS1398CW5A3">https://military-fasteners.com/rivets/NAS1398CW5A3</a> and selecting the property of t