

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398CW5AB3
Minimum Qty (MOQ):	100
NSN:	5320-01-585-2719
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1398CW5AB3 Specifications

Fastener Length:	0.326 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Locking Ring
Material Document And Classification:	Ams5731 Assn Std Single Material Response Stem
Material Document And Classification:	Ams5731 Assn Std Single Material Response Sleeve Or Ams5732 Assn Std Single Material Response Sleeve Or Ams5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Cadmium Sleeve
Surface Treatment Document And Classification:	Qq-p-416, Tyii, Cl2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398CW5AB3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.