

Description

Fastener Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398CW6A5
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-332-1518
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1398CW6A5 Specifications

Identification Code Color:	Natural
Fastener Length:	0.475 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Locking Ring
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5732 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Stem Or Ams 5732 Assn Std Single Material Response Stem Or Ams 5737 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve
Specification/standard Data:	80205-nas1398 Professional/Industrial Association Standard

How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398CW6A5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.