

Description

Fastener Length: 1-1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398CW6AB10
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-498-4146
Schedule B:	7318.23.0000
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS1398CW6AB10 Specifications

Fastener Length:	1.560 Inches Maximum
Head Style:	Brazier
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.563 Inches Minimum And 0.625 Inches Maximum
Part Name Assigned By Controlling Agency:	Rivet Blind, Protruding Head, Locked Spindle
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-416, Type II, Class 2 Fed Spec Single Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398CW6AB10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.