

**Description**

Fastener Length: 1-1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398CW6AB10
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-498-4146
Schedule B:	7318.23.0000
ECCN:	9A991



NO IMAGE  
AVAILABLE

## P/N NAS1398CW6AB10 Specifications

<b>Fastener Length:</b>	1.560 Inches Maximum
<b>Head Style:</b>	Brazier
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.563 Inches Minimum And 0.625 Inches Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Rivet Blind, Protruding Head, Locked Spindle
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-416, Type II, Class 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398CW6AB10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.