

Description

Cr Max Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1398CW6AB4
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-550-4744
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1398CW6AB4 Specifications

<b>Fastener Length:</b>	0.412 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Nominal
<b>Shank Diameter:</b>	0.190 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>End Item Identification:</b>	Apache Attack Helicopter
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Rivet-blind, Protruding Head, Locked Spindle
<b>Material:</b>	Aluminum Alloy 5056 Locking Ring
<b>Material:</b>	Aluminum Alloy 7075 Stem
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec 1st Material Response Overall
<b>Surface Treatment:</b>	Anodize Stem
<b>Surface Treatment:</b>	Cadmium Sleeve
<b>Specification/standard Data:</b>	80205-nas1398 Professional/Industrial Association Standard

## How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398CW6AB4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.