

Description

Cr Max Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1398CW6AB9
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-550-4739
Schedule B:	7318.23.0000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1398CW6AB9 Specifications

Fastener Length:	0.725 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Nominal
Shank Diameter:	0.190 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Apache Attack Helicopter
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Part Name Assigned By Controlling Agency:	Rivet-blind, Protruding Head, Locked Spindle
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 7075 Stem
Material:	Iron Alloy 660 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec 1st Material Response Overall
Surface Treatment:	Anodize Stem
Surface Treatment:	Cadmium Sleeve
Specification/standard Data:	80205-nas1398 Professional/Industrial Association Standard

How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398CW6AB9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.