

**Description**

NAS1398D5-2 Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398D52
Minimum Qty (MOQ):	25
NSN:	5320-00-821-8302
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in a sans-serif font.

NO IMAGE  
AVAILABLE

## P/N NAS1398D5-2 Specifications

<b>Identification Code Color:</b>	Yellow
<b>Fastener Length:</b>	0.263 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Heat Treatment:</b>	H-38 Strain Hardened Locking Ring
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Sleeve
<b>Material:</b>	Aluminum Alloy 5056 Locking Ring
<b>Material:</b>	Aluminum Alloy 7075 Stem
<b>Material:</b>	Aluminum Alloy 2017 Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Locking Ring
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Chromate Stem
<b>Surface Treatment:</b>	Anodize Sleeve Or Chromate Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398D5-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.