

**Description**

Blind Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS1398D5AB6        |
| Minimum Qty (MOQ):      | 10                  |
| NSN:                    | 5320-01-505-9297    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1398D5AB6 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.513 Inches Maximum   |
| <b>Head Style:</b>                                    | Universal  |
| <b>Head Height:</b>                                   | 0.067 Inches Minimum And 0.077 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.155 Inches Minimum And 0.159 Inches Maximum  |
| <b>Head Major Diameter:</b>                           | 0.296 Inches Minimum And 0.328 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>End Item Identification:</b>                       | Aircraft, Hornet F/a-18 (e/f)  |
| <b>Grip Length:</b>                                   | 0.313 Inches Minimum And 0.375 Inches Maximum  |
| <b>Special Features:</b>                              | For The Fully Serrated Spindle Series The Lock Ring May Be Integral With The Sleeve In Which Case The Lock Ring Is Of The Same Material And Finish As The Sleeve |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Locking Ring   |
| <b>Material:</b>                                      | Aluminum Alloy 7075 Stem   |
| <b>Material:</b>                                      | Aluminum Alloy 2017 Sleeve   |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Locking Ring  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Stem  |
| <b>Surface Treatment:</b>                             | Anodize Sleeve Or Chromate Sleeve  |
| <b>Surface Treatment:</b>                             | Anodize Stem Or Chromate Stem  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response Sleeve Or Mil-c-5541 Mil Spec Single Treatment Response Sleeve   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response Stem Or Mil-c-5541 Mil Spec Single Treatment Response Stem   |
| <b>Specification/standard Data:</b>                   | 80205-nas1398 Professional/Industrial Association Standard   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398D5AB6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.