

## **P/N NAS1398D5AB6**

### **Description**

Blind Rivet part number

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1398D5AB6

Minimum Qty (MOQ): 10

NSN: 5320-01-505-9297

Schedule B: 7616.10.3000

ECCN: EAR99

National Motor Freight: 013630, Alum Rivets



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1398D5AB6 Specifications

Fastener Length:	0.513 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Aircraft, Hornet F/a-18 (e/f)
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Special Features:	For The Fully Serrated Spindle Series The Lock Ring May Be Intregal With The Sleeve In Which Case The Lock Ring Is Of The Same Material And Finish As The Sleeve
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 7075 Stem
Material:	Aluminum Alloy 2017 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment:	Anodize Stem Or Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Sleeve Or Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Stem Or Mil-c-5541 Mil Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1398 Professional/industrial Association Standard

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1398D5AB6">https://military-fasteners.com/rivets/blind+rivets/NAS1398D5AB6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1398D5AB6">https://military-fasteners.com/rivets/blind+rivets/NAS1398D5AB6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1398D5AB6">https://military-fasteners.com/rivets/blind+rivets/NAS1398D5AB6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1398D5AB6">https://military-fasteners.com/rivets/NAS1398D5AB6</a> and selecting the quantity you want <a href="https://military-fasteners.com/rivets/NAS1398D5AB6">https://military-fasteners.com/rivets/NAS1398D5AB6</a> and selecting the property of t