

## **P/N NAS1398D6AB3**

### **Description**

Cr Max Rivet part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1398D6AB3

Minimum Qty (MOQ): 20 EA

NSN: 5320-01-552-5067

Schedule B: 7616.10.3000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1398D6AB3 Specifications

Fastener Length:	0.350 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Nominal
Shank Diameter:	0.190 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.375 Inches Nominal
Expansion Device:	Serrated Stem-type W
End Item Identification:	Aircraft,f-15
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Part Name Assigned By Controlling Agency:	Rivet, blind
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 7075 Stem
Material:	Aluminum Alloy 2017 Sleeve

## **How to Order**

Order this cr max rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1398D6AB3">https://military-fasteners.com/rivets/blind+rivets/NAS1398D6AB3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1398D6AB3">https://military-fasteners.com/rivets/blind+rivets/NAS1398D6AB3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1398D6AB3">https://military-fasteners.com/rivets/blind+rivets/NAS1398D6AB3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1398D6AB3">https://military-fasteners.com/rivets/NAS1398D6AB3</a> and selecting the quantity you want <a href="https://military-fasteners.com/rivets/NAS1398D6AB3">https://military-fasteners.com/rivets/NAS1398D6AB3</a> and selecting the property of the property of