

Description

Cr Max Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398D6AB4
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-517-0978
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1398D6AB4 Specifications

Head Style:	Universal
Head Height:	0.054 Inches Nominal
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight W/chamfered Tip
Head Major Diameter:	0.250 Inches Nominal
Grip Length:	0.250 Inches Maximum
Special Features:	May Be Chemical Film Coated
Material:	Aluminum Alloy 7075 Body
Material:	Aluminum Alloy 2017 Sleeve
Material Document And Classification:	Nas1398 Assn Std All Material Responses Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall

How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398D6AB4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.