

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1398D8A3
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-019-6566
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N NAS1398D8A3 Specifications

Fastener Length:	0.385 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.253 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.475 Inches Minimum And 0.525 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Shear Strength:	1580 Single Pounds Per Square Inch
Heat Treatment:	H-38 Strain Hardened Locking Ring
Material:	Aluminum Alloy 5056 Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
Specification/standard Data:	80205-nas1398 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398D8A3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.