

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398MW4A4
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-215-0435
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1398MW4A4 Specifications

Fastener Length:	0.385 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Material:	Nickel Alloy 400 Body Or Nickel Alloy R-405 Body
Material:	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material:	Nickel Alloy 400 Stem Or Nickel Alloy R-405 Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Body
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Stem
Surface Treatment:	Cadmium Body And Chromate Body
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Body
Specification/standard Data:	80205-nas1398 Professional/industrial Association Standard

How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398MW4A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.