

Description

Fastener Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398MW6A3
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-240-1723
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

P/N NAS1398MW6A3 Specifications

Fastener Length:	0.350 Inches Minimum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Material:	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material:	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
Material:	Nickel Alloy 400 Stem Or Nickel Alloy R-405 Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Sleeve
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Stem
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Sleeve
Specification/standard Data:	80205-nas1398 Professional/industrial Association Standard

How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398MW6A3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.