

Description

Fastener Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1398MW6A3
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-240-1723
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



\* See page 2 for technical characteristics

## P/N NAS1398MW6A3 Specifications

<b>Fastener Length:</b>	0.350 Inches Minimum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Material:</b>	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
<b>Material:</b>	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
<b>Material:</b>	Nickel Alloy 400 Stem Or Nickel Alloy R-405 Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Sleeve
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Stem
<b>Surface Treatment:</b>	Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Sleeve
<b>Specification/standard Data:</b>	80205-nas1398 Professional/industrial Association Standard

## How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398MW6A3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.