

**Description**

NAS1399C3A3 Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | NAS1399C3A3                               |
| Minimum Qty (MOQ):      | 25                                        |
| NSN:                    | 5320-01-392-2645                          |
| Schedule B:             | 7318.23.0000                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1399C3A3 Specifications

|                                                       |                                                                                                                                                             |
|-------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Fastener Length:</b>                               | 0.291 Inches Maximum                                                                                                                                        |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)                                                                              |
| <b>Shank Diameter:</b>                                | 0.093 Inches Minimum And 0.097 Inches Maximum                                                                                                               |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem                                                                                                                      |
| <b>Head Major Diameter:</b>                           | 0.175 Inches Minimum And 0.183 Inches Maximum                                                                                                               |
| <b>Expansion Device:</b>                              | Serrated Stem-type W                                                                                                                                        |
| <b>Grip Length:</b>                                   | 0.126 Inches Minimum And 0.187 Inches Maximum                                                                                                               |
| <b>Countersink Angle:</b>                             | 98.5 Degrees Minimum And 101.5 Degrees Maximum                                                                                                              |
| <b>Material:</b>                                      | Iron Alloy 660 Sleeve                                                                                                                                       |
| <b>Material:</b>                                      | Iron Alloy 660 Stem                                                                                                                                         |
| <b>Material:</b>                                      | Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring                                                                                            |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5732 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve |
| <b>Material Document And Classification:</b>          | Qq-n-281 Fed Spec All Material Responses Locking Ring                                                                                                       |
| <b>Surface Treatment:</b>                             | Passivate Sleeve                                                                                                                                            |
| <b>Surface Treatment:</b>                             | Passivate Stem                                                                                                                                              |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Sleeve                                                                                                           |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Stem                                                                                                             |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399C3A3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.