

P/N NAS1399C3A8

Description

NAS1399C3A8 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1399C3A8
Minimum Qty (MOQ):	100
NSN:	5320-01-543-1421
ECCN:	EAR99



^{*} See page 2 for technical characteristics

P/N NAS1399C3A8 Specifications

Fastener Length:	0.605 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.175 Inches Minimum And 0.183 Inches Maximum
End Item Identification:	F-22 Raptor
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Sleeve
Material Document And	Ams5731 Assn Std Single Material Response Sleeve Or Ams5732 Assn Std Single Material Response Sleeve Or Ams5737 Assn Std Single
Classification:	Material Response Sleeve
Surface Treatment:	Passivate Sleeve

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1399C3A8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.