

**Description**

Fastener Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1399C4A8
Minimum Qty (MOQ):	100
NSN:	5320-01-132-5336
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1399C4A8 Specifications

<b>Fastener Length:</b>	0.597 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Head Major Diameter:</b>	0.259 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.438 Inches Minimum And 0.500 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Cl A Fed Spec 1st Material Response Locking Ring Or Qq-n-281 Cl B Fed Spec 2nd Material Response Locking Ring

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399C4A8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.