

**Description**

Cr Max Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1399C4AB6
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-439-0834
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1399C4AB6 Specifications

<b>Fastener Length:</b>	0.510 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.225 Inches Nominal
<b>Expansion Device:</b>	Break Stem
<b>Grip Length:</b>	0.375 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment:</b>	Passivate Overall

## How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399C4AB6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.