

**Description**

Fastener Length: 19/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1399C4AB8                                |
| Minimum Qty (MOQ):      | 10 EA                                       |
| NSN:                    | 5320-01-132-5336                            |
| Schedule B:             | 7318.23.0000                                |
| ECCN:                   | 9A991                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1399C4AB8 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.597 Inches Maximum   |
| <b>Head Style:</b>                           | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)   |
| <b>Shank Diameter:</b>                       | 0.124 Inches Minimum And 0.128 Inches Maximum  |
| <b>Head Major Diameter:</b>                  | 0.259 Inches Maximum   |
| <b>Expansion Device:</b>                     | Serrated Stem-type W   |
| <b>Grip Length:</b>                          | 0.438 Inches Minimum And 0.500 Inches Maximum  |
| <b>Countersink Angle:</b>                    | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| <b>Material:</b>                             | Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring   |
| <b>Material Document And Classification:</b> | Qq-n-281 Cl A Fed Spec 1st Material Response Locking Ring Or Qq-n-281 Cl B Fed Spec 2nd Material Response Locking Ring |

## How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399C4AB8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.