

## Description

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1399C5A8
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-009-7239
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1399C5A8 Specifications

<b>Fastener Length:</b>	0.638 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.282 Inches Minimum And 0.290 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.438 Inches Minimum And 0.500 Inches Maximum
<b>Shear Strength:</b>	1490 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Iron Alloy 660 Body
<b>Material:</b>	Iron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5735 Assn Std Single Material Response Body Or Ams 5736 Assn Std Single Material Response Body Or Ams 5737 Assn Std Single Material Response Body
<b>Material Document And Classification:</b>	Ams 5736 Assn Std Single Material Response Stem
<b>Specification/standard Data:</b>	80205-nas1399 Professional/industrial Association Standard

## How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399C5A8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.