

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1399C5A8
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-009-7239
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N NAS1399C5A8 Specifications

Fastener Length:	0.638 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Shear Strength:	1490 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Iron Alloy 660 Body
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Body Or Ams 5736 Assn Std Single Material Response Body Or Ams 5737 Assn Std Single Material Response Body
Material Document And Classification:	Ams 5736 Assn Std Single Material Response Stem
Specification/standard Data:	80205-nas1399 Professional/Industrial Association Standard

How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399C5A8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.