

# **P/N NAS1399C5AB9**

## **Description**

Blind Rivet part number

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1399C5AB9

Minimum Qty (MOQ): 15 EA

NSN: 5320-01-535-4559

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1399C5AB9 Specifications

Fastener Length:	0.701 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	F-15e Center Fuse
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Special Features:	For The Fully Serrated Spindle Series The Lock Ring May Be Intregal With The Sleeve In Which Case The Lock Ring Is Of The Same Material And Finish Asthe Sleeve
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Locking Ring
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5732 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1399 Professional/industrial Association Standard

### **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1399C5AB9">https://military-fasteners.com/rivets/blind+rivets/NAS1399C5AB9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1399C5AB9">https://military-fasteners.com/rivets/blind+rivets/NAS1399C5AB9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1399C5AB9">https://military-fasteners.com/rivets/blind+rivets/NAS1399C5AB9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1399C5AB9">https://military-fasteners.com/rivets/NAS1399C5AB9</a> and selecting the quantity you want <a href="https://military-fasteners.com/rivets/NAS1399C5AB9">https://military-fasteners.com/rivets/NAS1399C5AB9</a> and selecting the your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1399C5AB9">https://military-fasteners.com/rivets/NAS1399C5AB9</a> and selecting the your cart y