

P/N NAS1399CW3-2

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1399CW32

Minimum Qty (MOQ): 10 EA

NSN: 5320-01-495-0280

Schedule B: 7318.16.0060

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N NAS1399CW3-2 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Head Major Diameter:	0.175 Inches Minimum And 0.183 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Locking Ring
Material Document And Classification:	Ams-5731 Assn Std Single Material Response Sleeve Or Ams-5732 Assn Std Single Material Response Sleeve Or Ams-5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams-5731 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Assn Std Single Material Response Locking Ring
Surface Treatment:	Cadmium Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416 Type Ii, Class 2 Fed Spec Single Treatment Response Sleeve
Specification/standard Data:	80205-nas1399 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1399CW3-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.