

Description

NAS1399CW3A2 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1399CW3A2
Minimum Qty (MOQ):	100
NSN:	5320-01-477-1315
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1399CW3A2 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Self-plugging
Head Major Diameter:	0.175 Inches Minimum And 0.183 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	1b Cmpu Blk; B-1b Bomber
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy Locking Ring
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams5731 Assn Std Single Material Response Stem
Material Document And Classification:	Ams5731 Assn Std Single Material Response Sleeve Or Ams5732 Assn Std Single Material Response Sleeve Or Ams5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Chromate Sleeve And Cadmium Sleeve
Surface Treatment Document And Classification:	Qq-p-416, Ty II, Cl 2 Fed Spec Single Treatment Response Sleeve
Specification/standard Data:	80205-nas1399 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399CW3A2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.