

Description

lock rivet, NAS1399

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1399CW3A3
Minimum Qty (MOQ):	100
NSN:	5320-01-520-7388
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1399CW3A3 Specifications

Head Style:	Countersunk W/ Reverse Chamfer
Head Height:	0.036 Inches Nominal
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Tubular
Head Major Diameter:	0.175 Inches Minimum And 0.183 Inches Maximum
End Item Identification:	New Man
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Astm-a434-2004 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-416c Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Sae-ams-qq-p-35 Assn Std Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399CW3A3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.