

Description

NAS1399CW3A4 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1399CW3A4
Minimum Qty (MOQ):	100
NSN:	5320-01-518-1413
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS1399CW3A4 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Pin-rivet, Tapered, Threaded
Head Major Diameter:	0.179 Inches Nominal
End Item Identification:	Fleet Support
Countersink Angle:	100.0 Degrees Nominal
Part Name Assigned By Controlling Agency:	Rivet-blind, 100 Degrees Flush Head, Locked Spindle
Special Features:	Spindle Has Full Serrations
Material:	Nickel Alloy 400 Locking Ring
Material:	Steel Corrosion Resisting Sleeve
Material:	Steel Corrosion Resisting Stem
Material Document And Classification:	Ams4731 Assn Std Single Material Response Sleeve Or Ams5732 Assn Std Single Material Response Sleeve Or Ams5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams5731 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Cadmium Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Type Ii Class 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399CW3A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.