

Description

NAS1399CW3A6

* Manufacturer certifications are shipped with your order FREE of charge

[Order this part online](#)**Additional Information**

SKU / Model:	NAS1399CW3A6
Minimum Qty (MOQ):	100
NSN:	5320-01-543-0128
Schedule B:	7318.23.0000
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N NAS1399CW3A6 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Pin-rievet, Tapered, Threaded
Head Major Diameter:	0.179 Inches Nominal
Tip Diameter:	0.094 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Part Name Assigned By Controlling Agency:	Rivet-blind, 100 Degrees Flush Head, Locked Spindle
Special Features:	Spindle Has Full Serations
Material:	Nickel Alloy 400 Locking Ring
Material:	Steel Corrosion Resisting Sleeve
Material:	Steel Corrosion Resisting Stem
Material Document And Classification:	Ams4731 Assn Std Single Material Response Sleeve Or Ams5732 Assn Std Single Material Response Sleeve Or Ams5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams5731 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Cadmium Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Type2 Class 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399CW3A6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.