

Description

NAS1399CW3A6

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1399CW3A6
Minimum Qty (MOQ):	100
NSN:	5320-01-543-0128
Schedule B:	7318.23.0000
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS1399CW3A6 Specifications

<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.094 Inches Nominal
<b>Shank Style:</b>	Pin-rievet, Tapered, Threaded
<b>Head Major Diameter:</b>	0.179 Inches Nominal
<b>Tip Diameter:</b>	0.094 Inches Nominal
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Part Name Assigned By Controlling Agency:</b>	Rivet-blind, 100 Degrees Flush Head, Locked Spindle
<b>Special Features:</b>	Spindle Has Full Serations
<b>Material:</b>	Nickel Alloy 400 Locking Ring
<b>Material:</b>	Steel Corrosion Resisting Sleeve
<b>Material:</b>	Steel Corrosion Resisting Stem
<b>Material Document And Classification:</b>	Ams4731 Assn Std Single Material Response Sleeve Or Ams5732 Assn Std Single Material Response Sleeve Or Ams5737 Assn Std Single Material Response Sleeve
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Locking Ring
<b>Surface Treatment:</b>	Cadmium Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type2 Class 2 Fed Spec Single Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399CW3A6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.