

**Description**

Fastener Length: 13/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1399CW4A2
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-525-4941
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1399CW4A2 Specifications

<b>Fastener Length:</b>	0.208 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.125 Inches Nominal
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.221 Inches Minimum And 0.229 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Steel Corrosion Resisting Sleeve
<b>Material Document And Classification:</b>	Ams5731 Assn Std 1st Material Response Sleeve Or Ams5732 Assn Std 2nd Material Response Sleeve Or Ams5737 Assn Std 3rd Material Response Sleeve
<b>Surface Treatment:</b>	Cadmium Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response Sleeve
<b>Specification/standard Data:</b>	80205-nas1399 Professional/industrial Association Standard

## How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399CW4A2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.