

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1399D5A4 |
| Minimum Qty (MOQ): | 25 EA |
| NSN: | 5320-00-007-6381 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N NAS1399D5A4 Specifications

| | |
|---|--|
| Fastener Length: | 0.388 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.155 Inches Minimum And 0.159 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.282 Inches Minimum And 0.290 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.258 Inches Maximum |
| Shear Strength: | 710 Single Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Heat Treatment: | H-38 Strain Hardened Locking Ring |
| Material: | Aluminum Alloy 5056 Locking Ring |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Locking Ring |
| Surface Treatment: | Anodize Overall Or Chromate Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399D5A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.