

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1399D5A8
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-298-6154
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N NAS1399D5A8 Specifications

Fastener Length:	0.638 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Shear Strength:	755 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Heat Treatment:	H-38 Strain Hardened Locking Ring
Material:	Aluminum Alloy 5056 Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Locking Ring
Specification/standard Data:	80205-nas1399 Professional/Industrial Association Standard

How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399D5A8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.