

Description

Fastener Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1399D6A7 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-01-013-7227 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N NAS1399D6A7 Specifications

| | |
|---|--|
| Fastener Length: | 0.600 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.186 Inches Minimum And 0.190 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.349 Inches Minimum And 0.357 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.376 Inches Minimum And 0.437 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Heat Treatment: | H-38 Strain Hardened Locking Ring |
| Material: | Aluminum Alloy 5056 Locking Ring |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Locking Ring |
| Surface Treatment: | Anodize Sleeve Or Chromate Sleeve |
| Surface Treatment: | Anodize Stem Or Chromate Stem |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Stem Or Mil-c-5541 Mil Spec 2nd Treatment Response Stem |
| Specification/standard Data: | 80205-nas1399 Professional/industrial Association Standard |

How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399D6A7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.