

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1399MW5A4
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-009-0598
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

P/N NAS1399MW5A4 Specifications

Fastener Length:	0.388 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.156 Inches Minimum And 0.159 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	1000 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy 400 Overall Or Nickel Alloy R-405 Overall
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Overall
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve
Specification/standard Data:	80205-nas1399 Professional/Industrial Association Standard

How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1399MW5A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.