



Military-Fasteners.com

P/N NAS1404-7

Description

Fastener Length: 55/64", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS14047
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-834-5959
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1404-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Minimum
Fastener Length:	0.863 Inches Nominal
Head Style:	Pan No. 2
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-5626 Mil Spec 3rd Material Response Or Mil-s-6049 Mil Spec 4th Material Response Or Mil-s-6098 Mil Spec 5th Material Response Or Mil-s-8503 Mil Spec 6th Material Response
Screw Surface Treatment:	Cadmium And Chromate
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1404 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1404-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.