

## Description

Thread Size: 1/8", Nut Height: 1/8", Head Width: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS142308                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5310-01-168-1767                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS1423-08 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3b  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Nut Style:</b>                                     | Hexagon   |
| <b>Nut Height:</b>                                    | 0.112 Inches Nominal  |
| <b>Drilled Hole Diameter:</b>                         | 0.034 Inches Minimum And 0.039 Inches Maximum   |
| <b>Hole Type And Quantity:</b>                        | 3 Drilled   |
| <b>Width Across Flats:</b>                            | 0.376 Inches Minimum  |
| <b>Thread Series:</b>                                 | Unjc  |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Hardness Rating:</b>                               | 34.0 Rockwell C Minimum And 38.0 Rockwell C Maximum   |
| <b>Nominal Thread Size:</b>                           | 0.164 Inches  |
| <b>Hole Configuration Style:</b>                      | Configuration B   |
| <b>Countersink Angle:</b>                             | 110.0 Degrees Nominal Both Ends   |
| <b>Bearing Surface Type:</b>                          | Chamfered Or Washer Faced   |
| <b>Bearing Surface Finish:</b>                        | 125.0 Microinches   |
| <b>Material:</b>                                      | Steel Comp 4130 Overall Or Steel Comp 4340 Overall  |
| <b>Material Document And Classification:</b>          | Mil-s-6758,cond D-1 Or D-4 Or F-4 Mil Spec 1st Material Response Overall Or Mil-s-5000,cond C-1 Or C-4 Mil Spec 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35,ty 2,cl 2 Fed Spec Single Treatment Response Overall  |
| <b>Specification/standard Data:</b>                   | 80205-nas1423 Professional/Industrial Association Standard  |

## How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.