

## P/N NAS1423-10LH

## **Description**

Thread Size: 5/8", Nut Height: 13/64", Head Width: 1

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS142310LH

Minimum Qty (MOQ): 5

NSN: 5310-00-458-2839

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1423-10LH Specifications

Thread Class:	3b
Thread Direction:	Left-hand
Nut Style:	Hexagon
Nut Height:	0.193 Inches Minimum And 0.213 Inches Maximum
Drilled Hole Diameter:	0.046 Inches Nominal
Hole Type And Quantity:	3 Drilled
Width Across Flats:	0.986 Inches Minimum And 1.002 Inches Maximum
Thread Series:	Unf
Thread Quantity Per Inch:	18
Hardness Rating:	34.0 Rockwell C Minimum And 38.0 Rockwell C Maximum
Nominal Thread Size:	0.625 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	110.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered
Bearing Surface Finish:	250.0 Microinches
Material:	Steel Comp 4130 Overall Or Steel Comp E4340 Overall
Material Document And Classification:	Mil-s-6758 Cond D1 Or F4 Mil Spec 1st Material Response Overall Or Mil-s-5000 @cond C1 Or C4 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

### **How to Order**

Order this plain hexagon nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423-10LH">https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423-10LH</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423-10LH">https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423-10LH</a> and selecting the