

**Description**

Thread: 3/4-16, drilled jam nut, thin, NAS1423 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS142312                                 |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5310-00-959-2066                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS1423-12 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Nut Style:</b>                                     | Hexagon  |
| <b>Nut Height:</b>                                    | 0.240 Inches Minimum And 0.260 Inches Maximum  |
| <b>Drilled Hole Diameter:</b>                         | 0.070 Inches Nominal   |
| <b>Hole Type And Quantity:</b>                        | 3 Drilled  |
| <b>Width Across Flats:</b>                            | 1.109 Inches Minimum And 1.127 Inches Maximum  |
| <b>Thread Series:</b>                                 | Unf  |
| <b>Thread Quantity Per Inch:</b>                      | 16   |
| <b>Hardness Rating:</b>                               | 34.0 Rockwell C Minimum And 38.0 Rockwell C Maximum  |
| <b>Nominal Thread Size:</b>                           | 0.750 Inches   |
| <b>Hole Configuration Style:</b>                      | Configuration B  |
| <b>Countersink Angle:</b>                             | 110.0 Degrees Nominal Nut  |
| <b>Bearing Surface Type:</b>                          | Chamfered Or Washer Faced  |
| <b>Bearing Surface Finish:</b>                        | 250.0 Microinches  |
| <b>Material:</b>                                      | Steel Comp 4130 Overall Or Steel Comp E4340 Overall Or Steel Comp 4340 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s6758 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall  |

## How to Order

Order this plain hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.