

Description

Thread Size: 3/4", Nut Height: 1/4", Head Width: 1-1/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS142312LH
Minimum Qty (MOQ):	1
NSN:	5310-01-256-9716
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1423-12LH Specifications

Thread Class:	3b
Thread Direction:	Left-hand
Nut Style:	Hexagon
Nut Height:	0.250 Inches Nominal
Drilled Hole Diameter:	0.069 Inches Minimum And 0.074 Inches Maximum
Hole Type And Quantity:	3 Drilled
Width Across Flats:	1.109 Inches Minimum And 1.127 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	16
Hardness Rating:	34.0 Rockwell C Minimum And 38.0 Rockwell C Maximum
Nominal Thread Size:	0.750 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	110.0 Degrees Nominal Both Ends
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Steel Comp 4130 Overall Or Steel Comp E4340 Overall
Material Document And Classification:	Mil-s-6758,cond D-1 Or D-4 Or F-4 Mil Spec 1st Material Response Overall Or Mil-s-5000,cond C-1 Or C-4 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1423 Professional/Industrial Association Standard

How to Order

Order this plain hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423-12LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.