

Description

Thread: 1"-12, thin drilled jam nut, NAS1423 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS142316
Minimum Qty (MOQ):	2
NSN:	5310-00-829-9982
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1423-16 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Nut Style:	Hexagon
Nut Height:	0.240 Inches Minimum And 0.260 Inches Maximum
Drilled Hole Diameter:	0.070 Inches Nominal
Hole Type And Quantity:	3 Drilled
Width Across Flats:	1.481 Inches Minimum And 1.502 Inches Maximum
Thread Series:	Unf
Thread Quantity Per Inch:	12
Hardness Rating:	34.0 Rockwell C Minimum And 38.0 Rockwell C Maximum
Nominal Thread Size:	1.000 Inches
Hole Configuration Style:	Configuration B
Countersink Angle:	110.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered
Bearing Surface Finish:	250.0 Microinches
Material:	Steel Comp 4130 Overall Or Steel Comp E4340 Overall
Material Document And Classification:	Mil-s-6758,cond D Mil Spec 1st Material Response Overall Or Mil-s-5000,cond C1 Mil Spec 2nd Material Response Overall Or Mil-s-5000,cond C4 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1423 Professional/industrial Association Standard

How to Order

Order this plain hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.