

Description



thread: 10-32, drilled, jam nut, thin, NAS1423 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS14233
Minimum Qty (MOQ):	10
NSN:	5310-01-077-3123
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1423-3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Nut Style:	Hexagon
Nut Height:	0.115 Inches Minimum And 0.135 Inches Maximum
Drilled Hole Diameter:	0.034 Inches Minimum And 0.039 Inches Maximum
Hole Type And Quantity:	3 Drilled
Width Across Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Hardness Rating:	34.0 Rockwell C Minimum And 38.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Hole Configuration Style:	Configuration B
Bearing Surface Type:	Chamfered
Bearing Surface Finish:	125.0 Microinches
Material:	Steel Comp 4130 Overall Or Steel Comp 4340 Overall
Material Document And Classification:	Mil-s-6758,cond D1 Or D4 Or F4 Mil Spec 1st Material Response Overall Or Mil-s-5000,cond C1 Or C4 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1423 Professional/industrial Association Standard

How to Order

Order this plain hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS1423-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.